

AFFORDABLE PERFORMANCE



WCE

Versatile Solid Carbide End Mills | METRIC

Authorized Distributor:



www.omnitool.ca

WIDIA 

Email: sales@omnitool.ca

Toll Free: 1-800-265-3541

Tel: (519) 622-3065 | Fax: (519) 622-3270

284 Pinebush Road Unit 1, Cambridge ON N1T 1Z6

WCE END MILLS



AFFORDABLE PERFORMANCE

The WCE solid end milling line features an advanced geometry wrapped into a versatile tool to enable material versatility for small-to-medium shops seeking a cost-effective solution to machine small batches.



WCE4

Metric: 3mm–20mm

- Sharp Edges
- Ball Nose
- Radiused
- Chamfered



WCE5

Metric: 4mm–20mm

- Chamfered
- Corner Radii

WCE End Mill

Versatile Solid Carbide End Mills • WCE4 & WCE5

The WCE platform packs a combination of high-performance and general-purpose features into one end mill family offered at an affordable price point in both 4- and 5-flute geometries.



WCE4 4-flute geometry combines the asymmetrical index and variable helix features at an affordable price while ensuring material and application versatility, including demanding operations like full slots and heavy cuts.



WCE5 5-flute geometry combines the unequal index with an elevated 38-degree helix feature at an affordable price for use in primarily Carbon Steel and Stainless Steel shouldering and side milling applications.

WCE End Mill Family Shared Features:

ECCENTRIC RELIEF

to provide vibration dampening and increase tool life on stainless steels.

6mm+ = eccentric relief

6mm- = faceted relief

CORE TAPER

for improved chip evacuation and tool stability.

AFFORDABLE PERFORMANCE

PRODUCT

GRADE
WU20PD

FLUTES
4, 5

DIAMETER RANGE

WCE4	WCE5
3–20mm	4–20mm

CORNER CONDITIONS

WCE4
Sharp Edges
Chamfered
Radiused
Ball Nose

WCE5
Chamfered
Corner Radii

INDUSTRY



MATERIALS

FIRST CHOICE



SECOND CHOICE



APPLICATIONS

WCE4



SIDE/
SHOULDER
MILLING
ROUGHING



SLOTTING
SQUARE
END



HELICAL
MILLING



RAMPING
BLANK



PLUNGE
MILLING



3D
PROFILING

WCE5



SIDE/
SHOULDER
MILLING
ROUGHING



HELICAL
MILLING



RAMPING
BLANK



TROCHOIDAL
MILLING

WCE4

VARIABLE HELIX

and asymmetrical index to reduce vibrations and increase overall cutting stability.

WCE5



UNEQUAL INDEX

to reduce vibration/chatter

38° HELIX

to increase performance in a variety of applications.

WCE4 • Series W401 • Sharp Edge • 4 Flute • Cylindrical Shank • Metric





- first choice
- alternate choice

WU20PE

order #	catalogue #	D1	D	length of cut Ap1 max	length L	Z U
6945502	W401M03003SZT	3,0	6	8,00	57	4
6945503	W401M04003SZT	4,0	6	11,00	57	4
6945504	W401M05003SZT	5,0	6	13,00	57	4
6945505	W401M06003SZT	6,0	6	13,00	57	4
6945548	W401M08004SZT	8,0	8	19,00	63	4
6945549	W401M10005SZT	10,0	10	22,00	72	4
6945684	W401M12006SZT	12,0	12	26,00	83	4
6945685	W401M16008SZT	16,0	16	32,00	92	4
6945686	W401M20009SZT	20,0	20	38,00	104	4

WCE4 • Series W401 • Sharp Edge • 4 Flute • Weldon® Shank • Metric





- first choice
- alternate choice

WU20PE

order #	catalogue #	D1	D	length of cut Ap1 max	length L	Z U
6945510	W401M03003SZW	3,0	6	8,00	57	4
6945541	W401M04003SZW	4,0	6	11,00	57	4
6945542	W401M05003SZW	5,0	6	13,00	57	4
6945543	W401M06003SZW	6,0	6	13,00	57	4
6945562	W401M08004SZW	8,0	8	19,00	63	4
6945563	W401M10005SZW	10,0	10	22,00	72	4
6945690	W401M12006SZW	12,0	12	26,00	83	4
6945691	W401M16008SZW	16,0	16	32,00	92	4
6945692	W401M20009SZW	20,0	20	38,00	104	4

WCE4 • Series W401 • Chamfered • 4 Flute • Cylindrical Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	length of cut Ap1 max	length L	BCH	Z U
6945506	W401M03003CAT	3,0	6	8,00	57	0,20	4
6945507	W401M04003CAT	4,0	6	11,00	57	0,20	4
6945508	W401M05003CAT	5,0	6	13,00	57	0,30	4
6945509	W401M06003CAT	6,0	6	13,00	57	0,40	4
6945550	W401M08004CAT	8,0	8	19,00	63	0,40	4
6945561	W401M10005CET	10,0	10	22,00	72	0,50	4
6945687	W401M12006CET	12,0	12	26,00	83	0,50	4
6945688	W401M16008CET	16,0	16	32,00	92	0,50	4
6945689	W401M20009CET	20,0	20	38,00	104	0,50	4

WCE4 • Series W401 • Chamfered • 4 Flute • Weldon® Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	length of cut Ap1 max	length L	BCH	Z U
6945544	W401M03003CAW	3,0	6	8,00	57	0,20	4
6945545	W401M04003CAW	4,0	6	11,00	57	0,20	4
6945546	W401M05003CAW	5,0	6	13,00	57	0,30	4
6945547	W401M06003CAW	6,0	6	13,00	57	0,40	4
6945564	W401M08004CAW	8,0	8	19,00	63	0,40	4
6945565	W401M10005CEW	10,0	10	22,00	72	0,50	4
6945693	W401M12006CEW	12,0	12	26,00	83	0,50	4
6945694	W401M16008CEW	16,0	16	32,00	92	0,50	4
6945695	W401M20009CEW	20,0	20	38,00	104	0,50	4

WCE4 • Series W4N1 • Radiused • 4 Flute • Necked • Cylindrical Shank • Metric





● first choice
○ alternate choice

WU20PE

order #	catalogue #	D1	D	D3	length of cut Ap1 max	length L	L3	Re	Z U
6945620	W4N1M03003RAT	3,0	6	2,82	8,00	57	15,00	0,20	4
6945631	W4N1M04003RAT	4,0	6	3,76	11,00	57	16,00	0,20	4
6945632	W4N1M04003RET	4,0	6	3,76	11,00	57	16,00	0,50	4
6945633	W4N1M05003RAT	5,0	6	4,70	13,00	57	18,00	0,20	4
6945634	W4N1M05003RET	5,0	6	4,70	13,00	57	18,00	0,50	4
6945635	W4N1M05003RJT	5,0	6	4,70	13,00	57	18,00	1,00	4
6945636	W4N1M06003RET	6,0	6	5,64	13,00	57	21,00	0,50	4
6945638	W4N1M06003RHT	6,0	6	5,64	13,00	57	21,00	1,50	4
6945637	W4N1M06003RJT	6,0	6	5,64	13,00	57	21,00	1,00	4
6945640	W4N1M08004RET	8,0	8	7,52	19,00	63	27,00	0,50	4
6945642	W4N1M08004RHT	8,0	8	7,52	19,00	63	27,00	1,50	4
6945641	W4N1M08004RJT	8,0	8	7,52	19,00	63	27,00	1,00	4
6945643	W4N1M08004RKT	8,0	8	7,52	19,00	63	27,00	2,00	4
6945644	W4N1M10005RET	10,0	10	9,40	22,00	72	32,00	0,50	4
6945646	W4N1M10005RHT	10,0	10	9,40	22,00	72	32,00	1,50	4
6945645	W4N1M10005RJT	10,0	10	9,40	22,00	72	32,00	1,00	4
6945647	W4N1M10005RKT	10,0	10	9,40	22,00	72	32,00	2,00	4
6945128	W4N1M12006RET	12,0	12	11,28	26,00	83	38,00	0,50	4
6945130	W4N1M12006RHT	12,0	12	11,28	26,00	83	38,00	1,50	4
6945129	W4N1M12006RJT	12,0	12	11,28	26,00	83	38,00	1,00	4
6945481	W4N1M12006RKT	12,0	12	11,28	26,00	83	38,00	2,00	4
6945482	W4N1M12006RQT	12,0	12	11,28	26,00	83	38,00	4,00	4
6945483	W4N1M16008RJT	16,0	16	15,04	32,00	92	44,00	1,00	4
6945484	W4N1M16008RKT	16,0	16	15,04	32,00	92	44,00	2,00	4
6945485	W4N1M16008RPT	16,0	16	15,04	32,00	92	44,00	3,00	4
6945486	W4N1M16008RQT	16,0	16	15,04	32,00	92	44,00	4,00	4
6945487	W4N1M20009RJT	20,0	20	18,80	38,00	104	53,00	1,00	4
6945488	W4N1M20009RKT	20,0	20	18,80	38,00	104	53,00	2,00	4
6945489	W4N1M20009RPT	20,0	20	18,80	38,00	104	53,00	3,00	4
6945490	W4N1M20009RQT	20,0	20	18,80	38,00	104	53,00	4,00	4



WCE4 • Series W4N1 • Chamfered • 4 Flute • Necked • Weldon® Shank • Metric



WU20PE

order #	catalogue #	D1	D	D3	length of cut	length	L3	BCH	Z U
					Ap1 max	L			
7006950	W4N1M03003CAW	3,0	6	2,82	8,00	57	15,00	0,15	4
7007001	W4N1M04003CAW	4,0	6	3,76	11,00	57	16,00	0,15	4
7007002	W4N1M05003CAW	5,0	6	4,70	13,00	57	18,00	0,15	4
7007003	W4N1M06003CAW	6,0	6	5,64	13,00	57	21,00	0,15	4
7007004	W4N1M08004CAW	8,0	8	7,52	19,00	63	27,00	0,20	4
7007005	W4N1M10005CAW	10,0	10	9,40	22,00	72	32,00	0,20	4
7006070	W4N1M12006CAW	12,0	12	11,28	26,00	83	38,00	0,20	4
7006091	W4N1M16008CYW	16,0	16	15,04	32,00	92	44,00	0,35	4
7006092	W4N1M20009CYW	20,0	20	18,80	38,00	104	53,00	0,35	4
7006093	W4N1M2500ACYW	25,0	25	23,50	45,00	121	75,00	0,35	4

WCE4 • Series W411 • Chamfered • 4 Flute • Long Length • Cylindrical Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	length of cut	length	BCH	Z U
				Ap1 max	L		
6946013	W411M06013CAT	6,0	6	32,00	76	0,40	4
6946014	W411M08014CAT	8,0	8	32,00	87	0,40	4
6946015	W411M10015CET	10,0	10	38,00	89	0,50	4
6946046	W411M12016CET	12,0	12	51,00	100	0,50	4
6946047	W411M16018CET	16,0	16	57,00	125	0,50	4
6946048	W411M20019CET	20,0	20	57,00	125	0,50	4

WCE4 • Series W4NB • Ball Nose • 4 Flute • Cylindrical Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	D3	length of cut Ap1 max	length L	L3	Z U
6945882	W4NBM05003RBT	5,0	6	4,70	13,00	57	18,00	4
6945883	W4NBM06003RBT	6,0	6	5,64	13,00	57	21,00	4
6945886	W4NBM08004RBT	8,0	8	7,52	19,00	63	27,00	4
6945887	W4NBM10005RBT	10,0	10	9,40	22,00	72	32,00	4
6945895	W4NBM12006RBT	12,0	12	11,28	26,00	83	30,00	4
6945896	W4NBM16008RBT	16,0	16	15,04	32,00	92	38,00	4
6945897	W4NBM20009RBT	20,0	20	18,80	38,00	104	50,00	4

WCE4 • Series W4NB • Ball Nose • 4 Flute • Weldon® Shank • Metric






WU20PE




- first choice
- alternate choice

order #	catalogue #	D1	D	D3	length of cut Ap1 max	length L	L3	Z U
6945884	W4NBM05003RBW	5,0	6	4,70	13,00	57	18,00	4
6945885	W4NBM06003RBW	6,0	6	5,64	13,00	57	21,00	4
6945888	W4NBM08004RBW	8,0	8	7,52	19,00	63	27,00	4
6945889	W4NBM10005RBW	10,0	10	9,40	22,00	72	32,00	4
6945898	W4NBM12006RBW	12,0	12	11,28	26,00	83	30,00	4
6945899	W4NBM16008RBW	16,0	16	15,04	32,00	92	38,00	4
6945900	W4NBM20009RBW	20,0	20	18,80	38,00	104	50,00	4

Application Data • WCE4 Side Milling • Slotting • Metric

Material Group																							
	Side Milling		Slotting	WU20PE			Recommended feed per tooth (fz = mm/th) for side milling (A). For slotting (B), reduce fz by 20%.																
				Cutting Speed – Vc m/min				D1 – Diameter															
	ap	ae	ap	min	Start	max	mm	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0				
P	0	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	1	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	2	ap1max	0,4 x D1	1,0 x D1	140	165	190	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	3	ap1max	0,4 x D1	1,0 x D1	120	140	160	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	4	ap1max	0,4 x D1	0,75 x D1	90	120	150	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098			
	5	ap1max	0,4 x D1	1,0 x D1	60	80	100	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091			
M	1	ap1max	0,4 x D1	1,0 x D1	90	100	115	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	2	ap1max	0,4 x D1	1,0 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091			
	3	ap1max	0,4 x D1	1,0 x D1	60	65	70	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071			
K	1	ap1max	0,4 x D1	1,0 x D1	120	135	150	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	2	ap1max	0,4 x D1	1,0 x D1	110	125	140	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	3	ap1max	0,4 x D1	1,0 x D1	110	120	130	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091			
S	1	ap1max	0,4 x D1	0,3 x D1	50	70	90	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	2	ap1max	0,4 x D1	0,3 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061			
	3	ap1max	0,4 x D1	1,0 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061			
	4	ap1max	0,4 x D1	1,0 x D1	50	55	60	fz	0,011	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084			
H	1	ap1max	0,4 x D1	0,75 x D1	80	110	140	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098			
	2	ap1max	0,4 x D1	0,5 x D1	70	90	120	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071			

Application Data • WCE4 Side Milling • Slotting BN • Metric

Material Group																							
	Side Milling		Slotting	WU20PE			Recommended feed per tooth (fz = mm/th) for side milling (A). For slotting (B), reduce fz by 20%.																
				Cutting Speed – Vc m/min				D1 – Diameter															
	ap	ae	ap	min	Start	max	mm	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0				
P	0	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	1	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	2	ap1max	0,4 x D1	1,0 x D1	140	165	190	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	3	ap1max	0,4 x D1	1,0 x D1	120	140	160	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	4	ap1max	0,4 x D1	0,75 x D1	90	120	150	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098			
	5	ap1max	0,4 x D1	1,0 x D1	60	80	100	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091			
M	1	ap1max	0,4 x D1	1,0 x D1	90	100	115	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	2	ap1max	0,4 x D1	1,0 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091			
	3	ap1max	0,4 x D1	1,0 x D1	60	65	70	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071			
K	1	ap1max	0,4 x D1	1,0 x D1	120	135	150	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124			
	2	ap1max	0,4 x D1	1,0 x D1	110	125	140	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	3	ap1max	0,4 x D1	1,0 x D1	110	120	130	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091			
S	1	ap1max	0,4 x D1	0,3 x D1	50	70	90	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114			
	2	ap1max	0,4 x D1	0,3 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061			
	3	ap1max	0,4 x D1	1,0 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061			
	4	ap1max	0,4 x D1	1,0 x D1	50	55	60	fz	0,011	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084			
H	1	ap1max	0,4 x D1	0,75 x D1	80	110	140	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098			
	2	ap1max	0,4 x D1	0,5 x D1	70	90	120	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071			

Application Data • WCE4 Side Milling • Long • Metric

Material Group	Side Milling		Recommended feed per tooth (fz = mm/z) for side milling. No slotting operations recommended.																
			WU20PE			D1 – Diameter													
			Cutting Speed – Vc m/min			mm	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0	
			ap	ae	min	Start	max	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114
P	0	ap1max	0,2 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	1	ap1max	0,2 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,2 x D1	140	165	190	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	3	ap1max	0,2 x D1	120	140	160	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	4	ap1max	0,2 x D1	90	120	150	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	5	ap1max	0,2 x D1	60	80	100	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
6	ap1max	0,15 x D1	50	65	75	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071	
M	1	ap1max	0,2 x D1	90	100	115	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,2 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
	3	ap1max	0,2 x D1	60	65	70	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071
K	1	ap1max	0,2 x D1	120	135	150	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,2 x D1	110	125	140	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	3	ap1max	0,2 x D1	110	120	130	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
S	1	ap1max	0,1 x D1	50	70	90	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,1 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061
	3	ap1max	0,15 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061
	4	ap1max	0,15 x D1	50	55	60	fz	0,011	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084
H	1	ap1max	0,15 x D1	80	110	140	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	2	ap1max	0,15 x D1	70	90	120	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071

WCE • Adjustment Factor Table for Feed Calculation

To calculate application-specific cutting data, please use Kv coefficient table to the right for adaptation of cutting speed and KFz for feed, respectively.

$$Vc_{new} = Vc \cdot Kv$$

$$Fz_{new} = IPT \cdot KFz$$

Calculation example:

Application: D = 20mm; M2 material group;

Ae = 2mm

Cutting data recommendation: Vc = 80 m/min;

Fz = 0,089 mm/th

Adjustment coefficients: Ae = 2mm equals 10,0%;

Kv = 1,3; KFz = 1,64

Final cutting data recommendation:



Vc new = 80 * 1,3 = 104 m/min

Fz new = 0,089 * 1,64 = 0,146 mm/m

Metric

	Ae/D	2%	4%	5%	8%	10%	12%	20%	30%	40%	50%	100%
Speed Factor	Kv	1,9–3,3	1,45–2,7	1,45–2,3	1,45	1,3	1,3	1,2	1,1	1,0	0,9	0,8
Feed Factor	KFz	3,51	2,51	2,25	1,80	1,64	1,51	1,23	1,07	1,00	0,98	0,98

WCE5 • Series W501 • Chamfered • 5 Flute • Straight Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	length of cut Ap1 max	length L	BCH	Z U
7006956	W501M04003CAT	4,0	6	11,00	57	0,20	5
7006957	W501M05003CAT	5,0	6	13,00	57	0,30	5
7006958	W501M06003CAT	6,0	6	13,00	57	0,40	5
7007602	W501M08004CAT	8,0	8	19,00	63	0,40	5
7007603	W501M10005CET	10,0	10	22,00	72	0,50	5
7008716	W501M12006CET	12,0	12	26,00	83	0,50	5
7008717	W501M16008CET	16,0	16	32,00	92	0,50	5
7008718	W501M20009CET	20,0	20	38,00	104	0,50	5

WCE5 • Series W501 • Chamfered • 5 Flute • Weldon® Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	length of cut Ap1 max	length L	BCH	Z U
7006959	W501M04003CAW	4,0	6	11,00	57	0,20	5
7006960	W501M05003CAW	5,0	6	13,00	57	0,30	5
7007081	W501M06003CAW	6,0	6	13,00	57	0,40	5
7007604	W501M08004CAW	8,0	8	19,00	63	0,40	5
7007605	W501M10005CEW	10,0	10	22,00	72	0,50	5
7008719	W501M12006CEW	12,0	12	26,00	83	0,50	5
7008720	W501M16008CEW	16,0	16	32,00	92	0,50	5
7008731	W501M20009CEW	20,0	20	38,00	104	0,50	5

WCE5 • Series W5N1 • Radiused • 5 Flute • Necked • Straight Shank • Metric






WU20PE

● first choice
○ alternate choice

order #	catalogue #	D1	D	D3	length of cut Ap1 max	length L	L3	Re	Z U
7007606	W5N1M04003RAT	4,0	6	3,76	11,00	57	15,00	0,20	5
7007607	W5N1M04003RET	4,0	6	3,76	11,00	57	15,00	0,50	5
7007608	W5N1M05003RAT	5,0	6	4,70	13,00	57	17,00	0,20	5
7007609	W5N1M05003RET	5,0	6	4,70	13,00	57	17,00	0,50	5
7007610	W5N1M05003RJT	5,0	6	4,70	13,00	57	17,00	1,00	5
7007611	W5N1M06003RET	6,0	6	5,64	13,00	57	21,00	0,50	5
7007613	W5N1M06003RHT	6,0	6	5,64	13,00	57	21,00	1,50	5
7007612	W5N1M06003RJT	6,0	6	5,64	13,00	57	21,00	1,00	5
7007614	W5N1M08004RET	8,0	8	7,52	19,00	63	27,00	0,50	5
7007616	W5N1M08004RHT	8,0	8	7,52	19,00	63	27,00	1,50	5
7007615	W5N1M08004RJT	8,0	8	7,52	19,00	63	27,00	1,00	5
7007617	W5N1M08004RKT	8,0	8	7,52	19,00	63	27,00	2,00	5
7007618	W5N1M10005RET	10,0	10	9,40	22,00	72	32,00	0,50	5
7007620	W5N1M10005RHT	10,0	10	9,40	22,00	72	32,00	1,50	5
7007619	W5N1M10005RJT	10,0	10	9,40	22,00	72	32,00	1,00	5
7007621	W5N1M10005RKT	10,0	10	9,40	22,00	72	32,00	2,00	5
7008732	W5N1M12006RET	12,0	12	11,28	26,00	83	38,00	0,50	5
7008734	W5N1M12006RHT	12,0	12	11,28	26,00	83	38,00	1,50	5
7008733	W5N1M12006RJT	12,0	12	11,28	26,00	83	38,00	1,00	5
7008735	W5N1M12006RKT	12,0	12	11,28	26,00	83	38,00	2,00	5
7008736	W5N1M12006RQT	12,0	12	11,28	26,00	83	38,00	4,00	5
7008737	W5N1M16008RJT	16,0	16	15,04	32,00	92	44,00	1,00	5
7008738	W5N1M16008RKT	16,0	16	15,04	32,00	92	44,00	2,00	5
7008739	W5N1M16008RPT	16,0	16	15,04	32,00	92	44,00	3,00	5
7008740	W5N1M16008RQT	16,0	16	15,04	32,00	92	44,00	4,00	5
7008741	W5N1M20009RJT	20,0	20	18,80	38,00	104	55,00	1,00	5
7008742	W5N1M20009RKT	20,0	20	18,80	38,00	104	55,00	2,00	5
7008743	W5N1M20009RPT	20,0	20	18,80	38,00	104	55,00	3,00	5
7008744	W5N1M20009RQT	20,0	20	18,80	38,00	104	55,00	4,00	5

Application Data • WCE5 Side Milling • Slotting • Metric

Material Group																				
	Side Milling		Slotting		WU20PE			Recommended feed per tooth (fz = mm/th) for side milling (A). For slotting (B), reduce fz by 20%.												
					Cutting Speed – Vc m/min			D1 – Diameter												
	ap	ae	ap	min	Start	max	mm	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0		
P	0	ap1max	0,4 x D	0,3 x D	150	–	200	fz	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124	
	1	ap1max	0,4 x D	0,3 x D	150	–	200	fz	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124	
	2	ap1max	0,4 x D	0,3 x D	140	–	190	fz	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124	
	3	ap1max	0,4 x D	0,3 x D	120	–	160	fz	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114	
	4	ap1max	0,4 x D	0,3 x D	90	–	150	fz	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098	
	5	ap1max	0,4 x D	0,3 x D	60	–	100	fz	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091	
M	6	ap1max	0,4 x D	0,3 x D	50	–	75	fz	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071	
	1	ap1max	0,4 x D	0,3 x D	90	–	115	fz	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114	
	2	ap1max	0,4 x D	0,3 x D	60	–	80	fz	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091	
K	3	ap1max	0,4 x D	0,3 x D	60	–	70	fz	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071	
	1	ap1max	0,4 x D	0,3 x D	120	–	150	fz	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124	
	2	ap1max	0,4 x D	0,3 x D	110	–	140	fz	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114	
S	3	ap1max	0,4 x D	0,3 x D	110	–	130	fz	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091	
	1	ap1max	0,3 x D	0,2 x D	50	–	90	fz	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114	
	2	ap1max	0,3 x D	0,2 x D	25	–	40	fz	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061	
H	3	ap1max	0,4 x D	0,3 x D	60	–	80	fz	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091	
	4	ap1max	0,4 x D	0,3 x D	50	–	60	fz	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084	
H	1	ap1max	0,4 x D	0,3 x D	80	–	140	fz	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098	
H	2	ap1max	0,2 x D	0,3 x D	70	–	120	fz	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071	

NOTE: Lower value of cutting speed is used for high stock removal applications or for higher hardness (machinability) within group.
Higher value of cutting speed is used for finishing applications or for lower hardness (machinability) within group.
Above parameters are based on ideal conditions. For smaller taper machining centers, please adjust parameters accordingly on diameters greater than 12mm.
For better surface finish reduce feed per tooth.
Side milling applications - for longest reach (L3) tools, reduce Ae by 30%.
Slot milling applications - for longest reach (L3) tools, reduce Ae by 30%.

WCE • Adjustment Factor Table for Feed Calculation

To calculate application-specific cutting data, please use Kv coefficient table to the right for adaptation of cutting speed and KFz for feed, respectively.

Vc new = Vc * Kv
Fz new = IPT * KFz

Calculation example:
Application: D = 20mm; M2 material group;
Ae = 2mm
Cutting data recommendation: Vc = 80 m/min;
Fz = 0,089 mm/th
Adjustment coefficients: Ae = 2mm equals 10,0%;
Kv = 1,3; KFz = 1,64

Final cutting data recommendation:
Vc new = 80 * 1,3 = 104 m/min
Fz new = 0,089 * 1,64 = 0,146 mm/m

Metric

	Ae/D	2%	4%	5%	8%	10%	12%	20%	30%	40%	50%	100%
Speed Factor	Kv	1,9–3,3	1,45–2,7	1,45–2,3	1,45	1,3	1,3	1,2	1,1	1,0	0,9	0,8
Feed Factor	KFz	3,51	2,51	2,25	1,80	1,64	1,51	1,23	1,07	1,00	0,98	0,98





VERSATILE SOLID CARBIDE END MILLS

WORLD HEADQUARTERS

WIDIA

Kennametal Inc.
1600 Technology Way
Latrobe, PA 15650 USA
Tel: 1 800 979 4342
w-na.service@widia.com

EUROPEAN HEADQUARTERS

WIDIA

Kennametal Europe GmbH
Rheingoldstrasse 50
CH 8212 Neuhausen am Rheinfall
Switzerland
Tel: +41 52 6750 100
w-ch.service@widia.com

ASIA-PACIFIC HEADQUARTERS

WIDIA

Kennametal (Singapore) Pte. Ltd.
3A International Business Park
Unit #01-02/03/05, ICON@IBP
Singapore 609935
Tel: +65 6265 9222
w-sg.service@widia.com

INDIA HEADQUARTERS

WIDIA

Kennametal India Limited
CIN: L27109KA1964PLC001546
8/9th Mile, Tumkur Road
Bangalore - 560073
Tel: +91 80 2839 4321
w-in.service@widia.com

